

POLYMERIC MEMBRANE 650

Heavy Duty Acrylic Polymer For
Waterproofing of Terraces



Flexi-Crete PM 650 is a heavy duty, fiber reinforced
Terrace waterproofing coating.

Features of Flexi-Crete PM 650

- Ready to use, no mixing/dilution required, easy to apply.
- High tensile and elongation.
- Waterproofing and anti-root barrier..
- Crack bridging ability (Upto 2.0 mm width)
- UV resistant.
- Self primer. No need of additional primer.
- Light weight. Does not add any load on the structure.



Terraces coated with Flexi-Crete PM 650

Technical Data

Solids	~65%
Polymer Contents	~40%
Tensile Strength	>2N/M2
Elongation	200%
Algae & Fungal Growth	None
Chloride Permeability	Low
Approximate Coverage	10-12Sft/Kg

Marketed By-



A-229, Antophill Warehousing Complex,
Vidyalankar College Road,
Wadala (E), Mumbai - 400037, India.
Tel: +91-22-40655333
Fax: +91-22-24162 885
Email: polyflex@polyflex.co.in
Website: www.polyflex.co.in

The information indicated here is true to the best of our knowledge. However, no performance warranty/guaranty is implied on our products as the conditions of use and the skill and the quality of man power used for installation is beyond our control.